




ANTENNA EXPERTS

E-mail: info@antennaexperts.in Website: www.antennaexperts.in

Model AH-3842 3.8–4.2 GHz 17 dBic. Gain

MOBILE SATELLITE NEWS GATHERING SNG HELICAL ANTENNA

DESIGN FEATURES: The AH-3842 uses extended stubs to provide the greater gain while maintaining the wider beam-width making it perfect for satellite news gathering application. This high-gain low-profile antennas use Circular Polarization Antenna Technology - which delivers better penetration through obstruction and interference. This commercial grade mobile SNG antenna provides superior performance as compare to significantly larger and more expensive products. Our AH series helical antennas are smaller than conventional yagi antenna. The SNG antenna is highly suitable for mobile satellite news gathering systems. The AH-3842 SNG Helical Antenna is supplied with a specially designed mounting arrangement for steering the antenna in both planes, over 360 Degrees in Azimuth and 90 Degrees in Elevation for terrestrial and satellite links.



CONSTRUCTIONS: The AH-3842, like all our AH series helical antennas, utilizes circular polarization to minimize the effects of multipath interference. Both Right Hand Circular Polarized (RHCP) and Left Hand Circular Polarized (LHCP) SNG helical antenna models are available. The AH-3842 SNG Helical Antenna is light weight, broadband and rugged helical antennas, supplied with fiberglass radome to protect the antenna from environment. Cylindrical enclosure is used for low wind loading and for minimal effect of ice formation on the SNG helical antenna operation as well as providing an aesthetically pleasing appearance.

ARRAY FORMATION: For higher gain requirement, the Helical antenna can be supplied in DUAL stacked or QUAD stacked arrays with suitable power splitter/combiner cable harness.

ELECTRICAL SPECIFICATIONS:

Frequency Range	3800 - 4200 MHz.
Gain - Typical	17 dBic.
Bandwidth	Entire Band
Polarization	Circular - LHCP or RHCP
Input Impedance	50 Ohms.
Radiation Pattern	Directional
Horizontal Beam-width –Half Power Points	35 Degrees. Typical
Front to Back Ratio	18 dB. Typical
VSWR – Better Than	2 : 1
RF Power Handling Capacity	150 Watts.
Input Termination	N-Female

MECHANICAL SPECIFICATIONS:

Mounting Hardware	Marine Grade Stainless Steel
Gross Weight – Less Than	1 Kg.
Wind Rating	200 Km/Hr.
Overall Length	300 mm
Shipping Length	350 mm
Radiating Materials	High Quality Copper
Enclosure Materials	High Strength Fiber Glass
Enclosure Diameters	45 mm
Maximum Mount Pipe Diameter	52 mm (2 Inches)

ENVIRONMENTAL SPECIFICATIONS:

Operating Temperature	(-) 30 to +70 Degrees Celsius
Storage Temperature	(-) 40 to +80 Degrees Celsius
Humidity	0 to 95% RH

Please contact for further technical documentations like radiation patterns and VSWR curve.
Note: All information contained in the datasheet is subject to change without any prior notice.