



ANTENNA EXPERTS

E-mail: info@antennaexperts.in Website: www.antennaexperts.in

Model # AP-145019 1300 – 1600 MHz. 19 dBi. Gain

GRID PARABOLIC ANTENNA

DESIGN FEATURES: The AP-145019 grid parabolic antenna consists of full Parabolic reflector having a diameter of 0.9 Meter for use in point-to-point analogue and digital communication systems. The mounting arrangement of grid parabolic Antenna permits to change the polarization from horizontal to vertical and vice-versa.

CONSTRUCTIONS: Radiating elements and the dipole feed are made of high quality brass. The grid parabolic antenna operates at D.C. ground with low resistance discharge path for protection against lightning and immunity to noise. All the screws, nuts and bolts of grid parabolic antenna are of stainless steel.

TRACKING MECHANISM: The AP-145019 grid parabolic antenna supplied with elevation tracking mechanism where fine adjustments is necessary to optimize the signal strength of radio link.

ELECTRICAL SPECIFICATIONS:

Frequency Range	1300 - 1600 MHz.
Gain @ Mid Band	19 dBi.
Bandwidth	150 MHz.
Polarization	Vertical or Horizontal
Input Impedance	50 Ohms.
Radiation Pattern	Directional
Beam-width -3dB @ Mid Band	16 Degrees.
Front to Back Ratio	23 dB.
VSWR – Better than	1:1.5
RF Power Handling Capacity	250 Watts.
Input Termination	N-Female
Lightning Protection	Direct Ground

MECHANICAL SPECIFICATIONS:

Materials	All Aluminum
Mounting Hardware	Stainless Steel
Gross Weight	10 Kgs.
Wind Rating	200 Km/Hr.
Elevation Tracking	+/- 5 Degrees
Support Pipe Outer Diameter	25.4 mm (1 Inch)
Support Pipe Materials	Aluminum
Diameter of Parabolic Reflector	0.9 Meter
Radiating Materials	Brass
Grid Members Materials	Aluminum Pipe ½ Inch (12 mm)
Maximum Mount Pipe Diameter	52 mm (2 Inches)

ENVIRONMENTAL SPECIFICATIONS:

Operating Temperature	(-)30 to +70 Degrees Celsius
Storage Temperature	(-)40 to +80 Degrees Celsius
Humidity	0 to 95% RH

Note: All information contained in the datasheet is subject to change without any prior notice.