

## DIRECTIONAL YAGI ANTENNA

---

AY-150	134-174 MHz.	12 dBi. (10dBd) Gain
--------	--------------	----------------------

---

**DESIGN FEATURES:** Antenna Experts Yagi antenna design reflects innovative modern antenna construction. The unique design of the yagi antenna feed which works as matching device to keep the VSWR low resulting in increased efficiency of the yagi antenna. The mounting hardware supplied facilitates mounting on either vertical or horizontal members. The yagi antenna when packed comes with elements removed from the antenna boom for ease of packing and transportation. The small surface area on the yagi antenna minimizes wind resistance and conserves tower loading capacity.

**CONSTRUCTIONS:** Radiating elements, supporting booms and adjoining metal castings of yagi antenna have been constructed in high quality 6063T6 aluminum alloys to prevent corrosion. The yagi antenna uses special feed which eliminates the use of folded dipole. The Yagi antenna is supplied with N termination fixed on the driven element. This directional yagi antenna, comes factory tuned and does not require any field adjustment. This yagi antenna can be assembled at site with simple hand-tools.

### **ELECTRICAL SPECIFICATIONS:**

Frequency Range	134 - 174 MHz.
Gain	12 dBi. (10 dBd.)
Bandwidth	10 MHz.
Polarization	Vertical or Horizontal
Input Impedance	50 Ohms.
Radiation Pattern	Directional
Horizontal Beam-width –Half Power Points.	62 Degrees
Vertical Beam-width –Half Power Points.	52 Degrees
Front to Back Ratio	16 dB.
VSWR	1:1.5
RF Power Handling Capacity	250 Watts.
Input Termination	N-Female

### **MECHANICAL SPECIFICATIONS:**

Materials	6063T6 Aluminum
Mounting Hardware -Materials	Stainless Steel
Weight	4 Kgs.
Wind Rating	200 Km/Hr.
Overall Length	2.0 Meters.
Shipping Length	2.1 Meters.
Support Boom-Materials -Cross Section-Outer Diameter.	Aluminum-Square Tube -25.4mm
Elements-Materials-Cross Section-Outer Diameter.	Aluminum-Round Tube-19mm
Maximum Mount Pipe Diameter	52mm (2 Inches)

### **ENVIRONMENTAL SPECIFICATIONS:**

Operating Temperature	(-)30 to +70 Degrees Celsius
Storage Temperature	(-)40 to +80 Degrees Celsius
Humidity	0 to 95% RH