

ANTENNA EXPERTS

E-mail: info@antennaexperts.in Website: www.antennaexperts.in

Model # JCM7-1575

1550 - 1590 MHz.

7 dBi. Gain

High Gain Manpack Jammer Collinear Antenna

DESIGN FEATURES: The JCM7-1575 Jammer manpack collinear antenna is rugged all weather model, enclosed in a ABS radome, uses high quality brass radiating elements and does not require any field tuning or adjustments. The compact size of omni-directional antenna allows easy handling, shipping and highly suitable for transmitting, receiving including GPS L1 band without having the requirement of multiple antennas. Cylindrical enclosure is used for low wind loading and for minimal effect of ice formation on the antenna operation as well as providing an aesthetically pleasing appearance.

CONSTRUCTIONS: The high gain jammer manpack collinear antenna is supplied complete in assembled condition. This high gain jammer manpack antenna has smooth VSWR and constant Gain over the 1550-1590 MHz frequency band including GPS L1 band. The JC7-1575 jammer antenna consists of ultra corrosion resistant radiating elements and enclosed in ABS housing. The ABS has excellent transparency for Radio Signal and mechanically Robust to support extra mechanical strength to the antenna.

MOUNTING: The high gain jammer man pack collinear antenna is designed & supplied for Manpack application. The high gain jammer man pack antenna uses N-Male termination at the base so that same can be mounted directly on the equipment/transmitter.

NOTE: Part # JCM7-1575-S with spring fitted at base. Add 100mm in overall length and add 250 Grams in gross weight.

ELECTRICAL SPECIFICATIONS:

ELECTRICAL SI ECHTICATIONS.		
Frequency Range		1550 - 1590 MHz.
Gain - Typical		7 dBi.
Bandwidth		Entire Band
Polarization	_	Vertical
Input Impedance		50 Ohms.
Radiation Pattern		Omni-directional
-3dB. Vertical Beam-width		36 Degrees
VSWR – Better Than		1.5:1
RF Power Handling Capacity	8 0	50 Watts.
Input Termination		N-Male
MECHANICAL SPECIFICATIONS:		
Wind Rating		80 Km/Hr.
Mounting Type		Directly on Equipment/Tx.
Overall Length	GPS	500 mm
Shipping Length	L1	550 mm
Support Pipe Materials	Band	6063T6 Aluminum Alloy
Enclosure/Radome Diameter	Man	25 mm
Enclosure Materials	Pack	ABS
Radiators & Support Pipe	Ant.	6063T6 Aluminum Alloy
Gross Weight		350 Grams
Finish / Color		Olive Green
ENVIRONMENTAL SPECIFICATIONS:		
Operating Temperature		(-) 30 to +70 Degrees Celsius
Storage Temperature		(-) 40 to +80 Degrees Celsius
Humidity		0 to 95 % RH