

## **ANTENNA EXPERTS**

E-mail: info@antennaexperts.in Website: www.antennaexperts.in

Model # JCM9-2450

2400 - 2500 MHz.

9 dBi. Gain

## High Gain Manpack Jammer Collinear Antenna for ISM Wi-Fi Bluetooth Band

**DESIGN FEATURES:** The JCM9-2450 Jammer manpack collinear antenna is rugged all weather model, enclosed in a ABS radome, uses high quality brass radiating elements and does not require any field tuning or adjustments. The compact size of omni-directional antenna allows easy handling, shipping and highly suitable for transmitting, receiving ISM/Wi-Fi/Bluetooth bands without having the requirement of multiple antennas. Cylindrical enclosure is used for low wind loading and for minimal effect of ice formation on the antenna operation as well as providing an aesthetically pleasing appearance.

**CONSTRUCTIONS:** The jammer collinear antenna is supplied complete in assembled condition. This high gain jammer manpack antenna has smooth VSWR and constant Gain over the 2400-2500 MHz ISM/Wi-Fi/Bluetooth frequency bands. The JCM9-2450 jammer antenna consists of ultra corrosion resistant radiating elements and enclosed in ABS housing. The ABS has excellent transparency for Radio Signal and mechanically Robust to support extra mechanical strength to the antenna.

**MOUNTING:** The high gain man pack jammer collinear antenna is designed & supplied Man-pack application. The high gain man pack jammer antenna uses N-Male termination at the base so that same can be mounted directly on the equipment/transmitter. Optional: The antenna can be supplied with spring base if required.

## **ELECTRICAL SPECIFICATIONS:**

LEECTRICAL SPECIFICATIONS.		_
Frequency Range		2400 - 2500 MHz.
Gain		9 dBi.
Bandwidth		Entire Band
Polarization	A	Vertical
Input Impedance	N	50 Ohms.
Radiation Pattern	T	Omni-directional
-3dB. Vertical Beam-width	E	18 Degrees
VSWR – Better Than	N	1.5:1
RF Power Handling Capacity	N	50 Watts.
Input Termination	A	N-Male
MECHANICAL SPECIFICATIONS:		
Willia Rating	E	80 Km/Hr.
Mounting Type	X	Directly on Equipment/Tx.
Overall Length	P	500 mm
Shipping Length	Е	550 mm
Support Pipe iviaterials	R	6063T6 Aluminum Alloy
Enclosure/Radome Diameter	T	25 mm
Enclosure Materials	S	ABS
Radiators & Support Pipe		6063T6 Aluminum Alloy
Gross Weight		300 Grams
Finish / Color		Olive Green
ENVIRONMENTAL SPECIFICATIONS:		
Operating Temperature		(-) 30 to +70 Degrees Celsius
Storage Temperature		(-) 40 to +80 Degrees Celsius
Humidity		0 to 95 % RH
		·

Note: All information contained in the datasheet is subject to change without any prior notice.